Amendments to the Claims

1-12. (Cancelled)

13. (Currently amended) A method comprising:

receiving from a subscriber on an access network an authentication request, the

authentication request identifying the subscriber and identifying a designated service

provider from among a plurality of service providers;

sending the authentication request to the designated service provider;

receiving from the designated service provider an authentication response indicating

successful authentication of the subscriber by the designated service provider, wherein the

authentication response provides includes a service qualification, wherein the service

qualification that indicates at least one of (i) one or more types of services authorized for

the subscriber and (ii) one or more extents of service authorized for the subscriber:

responsive to the authentication response, assigning the subscriber to operate in a

designated layer of the access network set aside for subscribers that have been authenticated

by the designated service provider and to operate according to the service qualification; and

serving the subscriber in the designated layer of the access network.

The method of claim 13, wherein the access network is an IP 14. (Original)

network and the designated layer is an IP subnet, and wherein assigning the subscriber to

operate in the designated layer comprises assigning to the subscriber an IP address in the IP

subnet.

- 2 -

15. (Original) The method of claim 14, wherein serving the subscriber in the designated layer comprises handling communications with the subscriber according to a logic set established for the designated layer.

16. (Original) The method of claim 15, wherein handling communications with the subscriber according to the logic set established for the designated layer comprises: detecting a packet bearing the IP address assigned to the subscriber; and responsively applying the logic set to restrict transmission of the packet.

17. (Previously presented) The method of claim 13, wherein serving the subscriber in the designated layer of the access network comprises:

a gateway on the access network detecting a web page being sent to the subscriber; and

the gateway modifying the web page to include an advertisement for the designated service provider.

- 18. (Original) The method of claim 13, further comprising prompting the subscriber to provide the authentication request.
- 19. (Original) The method of claim 18, wherein prompting the subscriber for the authentication request comprises:

presenting to the subscriber a set of the plurality of service providers; and

prompting the subscriber to select a service provider from among the plurality

presented, wherein the subscriber selects the designated service provider from among the

plurality.

20. (Original) The method of claim 13, wherein the access network

comprises a wireless access network.

21. (Currently amended) A method carried out by an access network, the

method comprising:

prompting a first client station to select a service provider from among a plurality of

service providers, and receiving a signal from the first client station, indicating a first

selected service provider;

sending a first authentication request message for the first client station to the first

selected service provider, the first authentication request message indicating authentication

information for the first client station;

receiving a first authentication response message from the first selected service

provider, the first authentication response message indicating that first client station is

authenticated by the first selected service provider, wherein the first authentication response

provides includes a first service qualification that indicates at least one of (i) one or more

types of services authorized for the first client station and (ii) one or more extents of service

authorized for the first client station; and

in response to the first authentication response message, restricting the client station

to communications in a first logical layer of the access network associated with the first

selected service provider and according to the first service qualification.

- 4 -

22. (Currently amended) The method of claim 21, further comprising:

prompting a second client station to select a service provider from among a plurality

of service providers, and receiving a signal from the second client station, indicating a

second selected service provider;

sending a second authentication request message for the second client station to the

first selected service provider, the second authentication request message indicating

authentication information for the first client station;

receiving a second authentication response message from the second selected

service provider, the second authentication response message indicating that second client

station is authenticated by the second selected service provider, wherein the second

authentication response provides includes a second service qualification that indicates at

least one of (i) one or more types of services authorized for the second client station and (ii)

one or more extents of service authorized for the second client station; and

in response to the second authentication response message, restricting the second

client station to communications in a second logical layer of the access network associated

with the second selected service provider and according to the second service qualification.

23. (Currently amended) A communication system comprising:

means for prompting a first client station to select a service provider from among a

plurality of service providers, and for receiving a signal from the first client station,

indicating a first selected service provider;

- 5 -

means for sending a first authentication request message for the first client station to

the first selected service provider, the first authentication request message indicating

authentication information for the first client station;

means for receiving a first authentication response message from the first selected

service provider, the first authentication response message indicating that first client station

is authenticated by the first selected service provider, wherein the first authentication

response provides includes a first service qualification, where the first service qualification

that indicates at least one of (i) one or more types of services authorized for the first client

station and (ii) one or more extents of service authorized for the first client station; and

means for responding to the first authentication response message by restricting the

client station to communications in a first logical layer of the access network associated

with the first selected service provider and according to the first service qualification.

24. (Currently amended) The communication system of claim 23, further

comprising:

means for prompting a second client station to select a service provider from among

a plurality of service providers, and for receiving a signal from the second client station,

indicating a second selected service provider:

means for sending a second authentication request message for the second client

station to the first selected service provider, the second authentication request message

indicating authentication information for the first client station;

means for receiving a second authentication response message from the second

selected service provider, the second authentication response message indicating that

second client station is authenticated by the second selected service provider, wherein the

- 6 -

second authentication response provides includes a second service qualification, wherein

the second service qualification that indicates at least one of (i) one or more types of

services authorized for the second client station and (ii) one or more extents of service

authorized for the second client station; and

means for responding to the second authentication response message by restricting

the second client station to communications in a second logical layer of the access network

associated with the second selected service provider and according to the second service

qualification.

25. (New) The method of claim 15, further comprising:

before receiving the authentication response, assigning the subscriber to operate in a

default layer of the access network; and

handling communications in the default layer according to a default logic set.

26. (New) The method of claim 16, wherein handling communications with the

subscriber according to the logic set established for the designated layer comprises:

disallowing communications from the subscriber to outside of the access network.

27. (New) The method of claim 16, wherein handling communications with the

subscriber according to the logic set established for the designated layer comprises:

disallowing a predetermined type of communication from passing from the

subscriber to outside of the access network.

-7-

- 28. (New) The method of claim 15, wherein handling communications with the subscriber according to the logic set established for the designated layer comprises: detecting a web page being sent to an address on the designated layer; and injecting into the web page information specific to the designated service provider.
- 29. (New) The method of claim 28, wherein the information comprises an advertisement for the designated service provider.
- 30. (New) The method of claim 13, wherein the subscriber communicates via an air interface with the access network.